



Aria LED Vanity ARV Series

Features

Sleek contemporary wall mount vanity can be mounted horizontally above the mirror or vertically. Fixture is ADA compliant and has die-cast aluminum end caps with a frosted white acrylic diffuser. Power supply connection can be made in a standard J-box with a supplied 5" diameter J-box cover plate or can be made inside the housing without the need for a cover plate.

Construction

The wiring compartment is formed from .050" thick aluminum and is provided with keyhole mounting slots and wiring access. The decorative end caps are die cast aluminum. End caps are retained with thumbnuts for tool-less relamping.

Finish

All metal parts are plated in the following finishes:
• Satin Nickel (SN) • Oil-Rubbed Bronze (RB)

Diffuser

Diffuser is .100" thick-frosted white extruded acrylic with internal linear prisms.

Electrical

This unit is direct wired with a low voltage electronic LED driver rated for 120-277V universal voltage.

Lamping

Fixture includes linear LED modules producing:
26" - 1000 source lumens
38" - 1400 source lumens
50" - 2100 source lumens
3000K (CCT). Rated for 50,000 Hrs LED life, 90 CRI.

Certification

All fixtures are ETL listed for damp locations.

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date of purchase.

Specifications and dimensions
subject to change without notice.

Ordering Information:

Satin Nickel	Oil-Rubbed Bronze	LED	Source Lumens	CCT	H	L	D	MC
ARV26041000L30MVSN	ARV26041000L30MVRB	20W	1000	3000K	2-1/2"	26-1/4"	4"	18"
ARV38041400L30MVSN	ARV38041400L30MVRB	30W	1400	3000K	2-1/2"	38"	4"	18"
ARV50042100L30MVSN	ARV50042100L30MVRB	40W	2100	3000K	2-1/2"	50"	4"	18"

LOCATION		DATE
PREPARED BY		QUANTITY
COMMENTS		FIXTURE TYPE
CATALOG NUMBER		

