



PELLA 13 / 16

FLUSH MOUNT CEILING

location:
DAMP

SPECIFICATIONS:

DESCRIPTION

Flush-mounted ceiling fixture, featuring contoured one-piece handcrafted glass diffuser.

LAMPING

LED: 16W/24W Integrated source, 120V, dimmable, 85+ CRI, 2800°K CCT, 30,000 hours, included.

DIFFUSER

Handcrafted glass diffuser in Opal Matte with outer surface in various decors.

Pella 13: 12.5" Dia. x 3" H

Pella 16: 15.75" Dia. x 3.25" H

CONSTRUCTION

Stamped aluminum fitter is powder coated white.

MOUNTING

Installs directly to a 4" octagonal outlet box, centered on fixture.

90°C supply wire required for incandescent lamping.

LABELS

UL or ETL Listed. Suitable for Damp Locations (interior use only).



CHALK

OPAL MATTE



CHERRY



OAK



For ordering information, see next page

All dimensions provided are nominal.
Allowance must be made for dimensional tolerance in handcrafted glasses.

REV 3/16




BESA LIGHTING

PELLA 13 / 16

FLUSH MOUNT CEILING

ORDERING:


Pella 13:



FIXTURES	-	LAMP OPTIONS
PELLA1307C Opal Matte		LED 16W LED 120V,
PELLA13CHC Cherry		1600 lumens
PELLA130KC Oak		
PELLA13KRC Chalk		

Ex. PELLA13CHC-LED
Pella 13 LED Ceiling, Cherry

Pella 16:



FIXTURES	-	LAMP OPTIONS
PELLA1607C Opal Matte		LED 24W LED 120V,
PELLA16CHC Cherry		2400 lumens
PELLA160KC Oak		
PELLA16KRC Chalk		

Ex. PELLA16CHC-LED
Pella 16 LED Ceiling, Cherry

Project Information: